NSN 5320-01-059-2012

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-059-2012 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.877 inches and 0.897 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches Lubrication: Cetyl alcohol **Grip Length:** 0.567 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** 294, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5320-01-059-2012

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0