## NSN 5320-01-059-2022

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-059-2022 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.073 inches and 1.093 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.078 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3326 inches and 0.3331 inches **Shank Style: Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** 0.448 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Nodized ti shield 3 73197 or anodize tiodize type 2 73197 military standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-059-2022

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0