
# NSN 5320-01-059-2024

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.935 inches and 0.955 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

## Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.2095 inches and 0.2100 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Lubrication:

Dry film and cetyl alcohol

## Grip Length:

0.510 inches

# Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

## Shear Strength:

95000 single pounds per square inch

## Material:

Titanium alloy

## **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Anodize

## Surface Treatment Specification:

Nodized ti shield 3 73197 or anodize tiodize type 2 73197 military standard single treatment response

# **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-059-2024

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

