NSN 5320-01-059-3450

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-059-3450 **Thread Direction:** Right-hand Fastener Length: Between 1.098 inches and 1.118 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.399 inches **Grip Length:** Between 0.689 inches and 0.750 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees Material: Steel comp 8740 or steel comp e4340 or steel comp 4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5000 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses **Thread Series Designator:** Unjf **Specification Data:** 80205-nas4452 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A528u0

No

NSN 5320-01-059-3450

Pin-rivet - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.