
## NSN 5320-01-059-3634

Pin-rivet - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.659 inches and 0.679 inches

## Head Style:

Flush countersunk

## Width Between Flats:

Between 0.1582 inches and 0.1617 inches

## Shank Diameter:

Between 0.3740 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.588 inches

## Grip Length:

Between 0.126 inches and 0.188 inches

## Thready Qty Per Inch (tpi):

24

## Thread Size:

0.375 inches

## Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Chlorine free cetyl alcohol

#### Material:

Titanium alloy

#### Material Specification:

Ams 4967 assn standard single material response

#### **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas 4452 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-059-3634

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

