## NSN 5320-01-060-4735

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-060-4735 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.190 inches and 1.210 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Grip Length:** Between 0.870 inches and 0.880 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.203 inches **Shear Strength:** 6130 double pounds per square inch Material: Steel comp e4340 or steel comp 4340 **Material Specification:** II-s-5000 military standard 10th material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1, class 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-060-4735

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0