# NSN 5320-01-063-2431

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-063-2431

**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.598 inches and 0.618 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.061 inches and 0.069 inches

### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2485 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.398 inches and 0.413 inches

#### Grip Length:

Between 0.189 inches and 0.250 inches

# Thready Qty Per Inch (tpi):

28

#### Thread Size:

0.250 inches

#### Shear Strength:

156000 single pounds per square inch

#### Material:

Steel comp h11

#### **Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

#### Surface Treatment:

Zinc

# Surface Treatment Specification:

Qq-z-325, type 1, cl 3 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# **Specification Data:**

80205-nas4450 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

--



# NSN 5320-01-063-2431

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

