NSN 5320-01-064-7244

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-064-7244 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.050 inches and 2.070 inches **Head Style:** Err-090 **Head Height:** Between 0.103 inches and 0.115 inches Width Between Flats: Between 0.2207 inches and 0.2242 inches **Shank Diameter:** Between 0.4985 inches and 0.4995 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.735 inches and 0.770 inches Lubrication: Cetyl alcohol **Grip Length:** 1.380 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response or ams 5628 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-064-7244

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.