# NSN 5320-01-065-8861

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-065-8861



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.440 inches and 1.460 inches

#### Head Style:

Flush countersunk

## Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

#### 0.3536 inches

Lubrication:

Cetyl alcohol

## Grip Length:

1.130 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

## **Countersink Angle:**

100.0 degrees

#### **Heat Treatment:**

T-6 solution heat treated

## Material:

Aluminum alloy 7075

## **Material Specification:**

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

#### Surface Treatment:

Anodize

## Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-065-8861

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.

