## NSN 5320-01-066-1968

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-066-1968 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.377 inches and 1.397 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.3536 inches Lubrication: Cetyl alcohol **Grip Length:** 1.067 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Special Features:** Dye color natural **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5320-01-066-1968

Pin-rivet - Page 2 of 2



ι	Jn	it	Of	Measure:	•

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.