

View Online at <https://aerobasegroup.com/nsn/5320-01-066-6781>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.228 inches and 0.230 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

0.385 inches

**Expansion Device:**

Threaded stem

**Lubrication:**

Grease film or dry film or wax or cetyl alcohol

**Grip Length:**

Between 0.470 inches and 0.531 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c nut and 43.0 rockwell c nut

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve

**Surface Treatment:**

Cadmium sleeve and passivate sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nut or nas 672 assn standard 2nd treatment response nut and qq-p-416 federal specification 3rd treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.