NSN 5320-01-066-6787

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-066-6787 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.614 inches and 0.634 inches **Head Style:** Err-090 **Head Height:** Between 0.055 inches and 0.060 inches Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.306 inches and 0.322 inches Lubrication: Cetyl alcohol **Grip Length:** 0.317 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Color to p of head blue Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response or ams 5731 assn standard single material response **Surface Treatment:** Cadmium and chromate

Unjc

Surface Treatment Specification:

Thread Series Designator:

Qq-p-416, type 1, cl 3 federal specification single treatment response

NSN 5320-01-066-6787

Pin-rivet - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0