NSN 5320-01-068-1244

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-068-1244

Thread Class:

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.227 inches and 1.247 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.193 inches and 0.196 inches
Shank Style:
Blind rivet, nut and bolt (assembly)
Head Major Diameter:
0.2514 inches
Expansion Device:
Threaded mandrel
Grip Length:
0.938 inches
Thready Qty Per Inch (tpi):
40
Thread Size:
0.125 inches
Shear Strength:
95000 single pounds per square inch
Countersink Angle:
100.0 degrees
Material:
Steel comp 431 expander
Material Specification:
Ams 5731 assn standard single material response sleeve
Precious Material:
Silver
Surface Treatment:
Silver expander
Surface Treatment Specification:
Qq-s-365, gr b federal specification single treatment response expander
Thread Series Designator:
Unjc
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5320-01-068-1244

Blind Rivet - Page 2 of 2



Demi			

No

Fiig:

A040a0