NSN 5320-01-068-1339

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-068-1339

Thread Class:

3a
Thread Direction:
Right-hand

Fastener Length:

Between 0.507 inches and 0.527 inches

Head Style:

Err-090

Head Height:

Between 0.039 inches and 0.047 inches

Width Between Flats:

Between 0.0635 inches and 0.0645 inches

Shank Diameter:

Between 0.1625 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.245 inches and 0.257 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.189 inches and 0.250 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Shear Strength:

156000 single pounds per square inch

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas4450 professional/industrial association standard

Shelf Life:

N/a

NSN 5320-01-068-1339

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0