

View Online at <https://aerobasegroup.com/nsn/5320-01-068-5546>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.227 inches and 1.247 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.059 inches and 0.069 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2641 inches and 0.2651 inches

**Shank Style:**

**Head Major Diameter:**

Between 0.387 inches and 0.412 inches

**Grip Length:**

0.817 inches

**Features Provided:**

Sealant vent groove

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.2501 inches

**Shear Strength:**

95000 single pounds per square inch

**Special Features:**

Must be used with wet sealant or with lubed collars

**Material:**

Steel comp 8740 or steel comp 4140 or steel comp 4340 or steel comp e4340

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-5000 military specification 3rd material response or mil-s-5000 military specification 4th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.