# NSN 5320-01-070-3025

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-070-3025

Head	Ctvi	

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

#### **Shank Diameter:**

Between 0.197 inches and 0.199 inches

## **Shank Style:**

Threaded self-plugging shank w/sleeve

### **Head Major Diameter:**

Between 0.2700 inches and 0.3016 inches

#### **Expansion Device:**

Threaded stem

#### Lubrication:

Wax or grease film or cetyl alcohol

#### **Grip Length:**

Between 0.220 inches and 0.281 inches

#### Hardness Rating:

39.0 rockwell c nut and 46.0 rockwell c nut

### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nut

# **Material Specification:**

Mil-s-5626 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-6758 military specification 3rd material response nut

#### **Surface Treatment:**

Passivate sleeve and cadmium sleeve

# **Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response nut

### Shelf Life:

N/a

# **Unit Of Measure:**

# Demilitarization:

No Fiig:

# A040a0

710 1000

# Mil-std (military Standard):

Mil-s-5626 spec.