## NSN 5320-01-072-4814

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-072-4814 **Thread Class: Thread Direction:** Right-hand **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.387 inches and 0.390 inches **Shank Style:** Blind rivet, nut and bolt (assembly) **Head Major Diameter:** Between 0.445 inches and 0.450 inches **Expansion Device:** Expander **Grip Length:** Between 0.4275 inches and 0.4475 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.500 inches **Countersink Angle:** Between 98.0 degrees and 102.0 degrees **Special Features:** Furnished without bolt **Heat Treatment:** Annealed sleeve Material: Steel comp 303 expander **Material Specification:** Qq-a-430 federal specification single material response sleeve **Surface Treatment:** Cadmium expander **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response expander **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5320-01-072-4814

Blind Rivet - Page 2 of 2



Fiig:

A040a0