NSN 5320-01-073-7056



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-073-7056 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.996 inches and 1.021 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3403 inches **Head Major Diameter:** 0.508 inches Tip Diameter: 0.3306 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.615 inches and 0.630 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Thread Size: 0.312 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** 8-32unjc-3b thread size, 0.280 in. Lg along the longitudinal axis from the head end, 0.120 in. Slot lg, 0.060 in. W located 0.220 in. From top of head to center of slot Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response

Surface Treatment:

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

Passivate

N/a

NSN 5320-01-073-7056

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0