NSN 5320-01-075-1013

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-075-1013

| Fastener Length: |
|--|
| Between 0.524 inches and 0.544 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.155 inches and 0.157 inches |
| Shank Style: |
| Drive pin |
| Head Major Diameter: |
| 0.250 inches |
| Expansion Device: |
| Drive stem-type h |
| Lubrication: |
| Dry film |
| Grip Length: |
| Between 0.478 inches and 0.540 inches |
| Min. Tensile Strength (psi): |
| 105000 pounds per square inch |
| Shear Strength: |
| 75000 single pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp 431 stem |
| Material Specification: |
| Mil-s-18732 military specification single material response stem |
| Surface Treatment: |
| Cadmium stem |
| Surface Treatment Specification: |
| Qq-p-416, type 1, class 3 federal specification single treatment response stem |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |

Mil-s-18732 spec.