## NSN 5320-01-077-0572

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-077-0572

## Thread Class:

Lh

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

0.845 inches

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

#### Shank Style:

Pin-rivet, tapered, threaded

## Head Major Diameter:

0.395 inches

Tip Diameter:

#### 0.268 inches

#### **Expansion Device:**

## Break stem

Lubrication:

Cetyl alcohol

## Grip Length:

Between 0.439 inches and 0.500 inches

## Thready Qty Per Inch (tpi):

32

## Hardness Rating:

43.5 rockwell c nut and 46.5 rockwell c nut

## Thread Size:

0.250 inches

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## **Special Features:**

Fastener length given is installed dimension

## Material:

Steel comp 8740 nut

## Material Specification:

Mil-s-6049 military specification 2nd material response nut

## Surface Treatment:

Cadmium sleeve

## Surface Treatment Specification:

Qq-p-416, type ii, class 3 federal specification 3rd treatment response sleeve

## Thread Series Designator:

Uns

## Shelf Life:

N/a

# NSN 5320-01-077-0572

Blind Rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.

