## NSN 5320-01-077-3940

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-077-3940 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.827 inches and 0.847 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2696 inches and 0.2701 inches **Shank Style: Head Major Diameter:** 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and solid film **Grip Length:** 0.322 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3, fscm 73197 mfr ref single treatment response or tiodize type 2, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

## NSN 5320-01-077-3940

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0