NSN 5320-01-077-6838

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-077-6838 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.947 inches and 0.967 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3326 inches and 0.3331 inches **Shank Style: Head Major Diameter:** 0.4739 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and solid film **Grip Length:** 0.322 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.3125 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3, fscm 73197 mfr ref single treatment response or ti0dize type 2, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

NSN 5320-01-077-6838

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0