

View Online at <https://aerobasegroup.com/nsn/5320-01-077-9088>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.415 inches and 1.435 inches

Head Style:

Err-090

Head Height:

Between 0.059 inches and 0.061 inches

Width Between Flats:

Between 0.095 inches and 0.097 inches

Shank Diameter:

Between 0.248 inches and 0.250 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.389 inches and 0.395 inches

Grip Length:

1.000 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

9300 double pounds per square inch

Material:

Steel

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.