NSN 5320-01-077-9088

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-077-9088 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.415 inches and 1.435 inches **Head Style:** Err-090 **Head Height:** Between 0.059 inches and 0.061 inches Width Between Flats: Between 0.095 inches and 0.097 inches **Shank Diameter:** Between 0.248 inches and 0.250 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.389 inches and 0.395 inches **Grip Length:** 1.000 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 9300 double pounds per square inch Material: Steel **Material Specification:** Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-077-9088

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.