NSN 5320-01-077-9797

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-077-9797 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.953 inches and 0.973 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2856 inches and 0.2867 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.426 inches Lubrication: Cetyl alcohol or cetyl alcohol, specification 305, hi-shear corporation and solid film **Grip Length:** 0.448 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Tiodize type 2, fscm 73197 mfr ref single treatment response or ti fin 400, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-077-9797

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0