

View Online at <https://aerobasegroup.com/nsn/5320-01-077-9797>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.953 inches and 0.973 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2856 inches and 0.2867 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.426 inches

**Lubrication:**

Cetyl alcohol or cetyl alcohol, specification 305, hi-shear corporation and solid film

**Grip Length:**

0.448 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Titanium alloy

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Tiodize type 2, fscm 73197 mfr ref single treatment response or ti fin 400, fscm 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0