## NSN 5320-01-077-9798

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-077-9798



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.947 inches and 0.967 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

## Shank Diameter:

Between 0.3487 inches and 0.3498 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.5051 inches

#### Lubrication:

Cetyl alcohol or cetyl alcohol, specification 305, hi-shear corporation and solid film

## Grip Length:

0.322 inches

## Thready Qty Per Inch (tpi):

24

## **Thread Size:**

0.3125 inches

#### Shear Strength:

95000 single pounds per square inch

## **Countersink Angle:**

100.0 degrees

#### Material:

Titanium alloy

## **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Anodize

## Surface Treatment Specification:

Tiodize type 2, fscm 73197 mfr ref single treatment response or ti fin 400, fscm 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-077-9798

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

