## NSN 5320-01-078-2407

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-078-2407 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.632 inches and 0.652 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0635 inches and 0.0645 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style: Head Major Diameter:** 0.256 inches **Grip Length:** Between 0.313 inches and 0.375 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 156000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjc **Specification Data:** 80205-nas4452 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-078-2407

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0