NSN 5320-01-078-4525

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-078-4525



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.683 inches and 0.708 inches

Head Style:

Flush countersunk

Shank Diameter:

0.326 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

0.494 inches

Tip Diameter:

0.3228 inches

Lubrication:

Cetyl alcohol and dry film

Grip Length:

Between 0.302 inches and 0.317 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1724 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5320-01-078-4525

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

