

View Online at <https://aerobasegroup.com/nsn/5320-01-079-6817>

Fastener Length:

Between 0.619 inches and 0.649 inches

Head Style:

Universal

Head Height:

Between 0.037 inches and 0.047 inches

Shank Diameter:

Between 0.155 inches and 0.159 inches

Shank Style:

Self-plugging

Head Major Diameter:

Between 0.296 inches and 0.328 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.376 inches and 0.500 inches

Material:

Steel comp 1006 mandrel or steel comp 1008 mandrel or steel comp 1009 mandrel or steel comp 1010 mandrel or steel comp 1011 mandrel or steel comp 1012 mandrel or steel comp 1013 mandrel or steel comp 1015 mandrel or steel comp 1016 mandrel or steel comp 1017 mandrel or steel comp 1018 mandrel or steel comp 1019 mandrel or steel comp 1020 mandrel or steel comp 1021 mandrel or steel comp 1022 mandrel or steel comp 1023 mandrel or steel comp 1524 mandrel or steel comp 1025 mandrel

Surface Treatment:

Zinc mandrel or cadmium mandrel or cadmium mandrel and chromate mandrel or cadmium mandrel and phosphate mandrel or phosphate mandrel

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response body or mil-c-5541 military specification 2nd treatment response body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.