

View Online at <https://aerobasegroup.com/nsn/5320-01-080-3815>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.587 inches and 2.612 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.454 inches and 0.470 inches

**Shank Diameter:**

0.9166 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Tip Diameter:**

0.8931 inches

**Lubrication:**

Cetyl alcohol and dry film

**Grip Length:**

Between 1.427 inches and 1.442 inches

**Width Across Flats:**

1.842 inches

**Thready Qty Per Inch (tpi):**

16

**Thread Size:**

0.750 inches

**Shear Strength:**

125000 single pounds per square inch

**Product Name:**

Pin-riquet, threaded, tapered, 12 point head, 7/8 diameter, shouldered drilled, 3/4-16 thread, 125 ksi fsu cres

**Special Features:**

Two drilled holes 90 degrees apart

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0