Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-080-9250

Fastener Length:

0.406 inches

Head Style:

Universal

Head Height:

Between 0.030 inches and 0.038 inches

Hole Diameter:

Between 0.084 inches and 0.090 inches

Shank Diameter:

Between 0.118 inches and 0.123 inches

Shank Style:

Tubular

Head Major Diameter:

Between 0.213 inches and 0.224 inches

Hole Depth:

0.094 inches

Shear Strength:

32000 double pounds per square inch

Material:

Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp

1020 or steel comp 1021 or steel comp 1022

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type2, class 2 federal specification all treatment responses

Specification Or Standard:

12 type and 3 class and e grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0