NSN 5320-01-083-0189

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-083-0189

0.655 inches Head Style: Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.092 inches and 0.097 inches Shank Style: Self-plugging high clinch shank Head Major Diameter: 0.183 inches Expansion Device:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.092 inches and 0.097 inches Shank Style: Self-plugging high clinch shank Head Major Diameter: 0.183 inches
Shank Diameter: Between 0.092 inches and 0.097 inches Shank Style: Self-plugging high clinch shank Head Major Diameter: 0.183 inches
Between 0.092 inches and 0.097 inches Shank Style: Self-plugging high clinch shank Head Major Diameter: 0.183 inches
Shank Style: Self-plugging high clinch shank Head Major Diameter: 0.183 inches
Self-plugging high clinch shank Head Major Diameter: 0.183 inches
Head Major Diameter: 0.183 inches
0.183 inches
Expansion Device:
Threaded stem
Lubrication:
Dry film
Grip Length:
Between 0.438 inches and 0.500 inches
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 305 stem
Material Specification:
Ms5731 assn standard single material response sleeve or ams5737 assn standard single material response sleeve
Surface Treatment:
Passivate stem
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response stem
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0