# NSN 5320-01-084-1959

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-084-1959

## Fastener Length:

Between 0.615 inches and 0.635 inches

#### Head Style:

Undersized oval countersunk

## Head Height:

Between 0.003 inches and 0.005 inches

## Shank Diameter:

Between 0.124 inches and 0.127 inches

#### Shank Style:

Straight w/radius chamfered tip

## Head Major Diameter:

Between 0.1739 inches and 0.1957 inches

## Head Minor Diameter:

0.134 mils and 0.144 centimeters

# **Countersink Height:**

0.0286 inches

#### **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

## Special Features:

Color violet

# Heat Treatment:

T-81 solution heat treated

#### Material:

Aluminum alloy 2219

# Material Specification:

Qq-a-430 federal specification single material response

# Surface Treatment:

Anodize

# Surface Treatment Specification:

Mil-a-8625, type 2, class 2 military specification single treatment response

#### Shelf Life:

N/a

# Unit Of Measure:

```
---
```

# Demilitarization:

No

Fiig:

A040a0

#### Mil-std (military Standard):

Mil-a-8625 spec.