# NSN 5320-01-084-1961

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-084-1961

## Fastener Length:

Between 0.740 inches and 0.760 inches

## Head Style:

Undersized oval countersunk

## Head Height:

Between 0.003 inches and 0.005 inches

## Shank Diameter:

Between 0.124 inches and 0.127 inches

#### Shank Style:

Straight w/radius chamfered tip

## Head Major Diameter:

Between 0.1739 inches and 0.1957 inches

## Head Minor Diameter:

0.134 mils and 0.144 centimeters

## **Countersink Height:**

0.0286 inches

## **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

## Special Features:

Color violet

## Heat Treatment:

T-81 solution heat treated

## Material:

Aluminum alloy 2219

## **Material Specification:**

Qq-a-430 federal specification single material response

## Surface Treatment:

Anodize

## Surface Treatment Specification:

Mil-a-8625, type 2, class 2 military specification single treatment response

## Shelf Life:

N/a

# Unit Of Measure:

```
--
```

## Demilitarization:

No

## Fiig:

A040a0

## Mil-std (military Standard):

Mil-a-8625 spec.