

View Online at <https://aerobasegroup.com/nsn/5320-01-084-4806>

Fastener Length:

Between 0.865 inches and 0.885 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.093 inches and 0.097 inches

Shank Style:

Straight w/radius chamfered tip

Head Major Diameter:

Between 0.1548 inches and 0.1900 inches

Shear Strength:

65000 single pounds per square inch

Countersink Angle:

Between 96.5 degrees and 101.5 degrees

Heat Treatment:

Annealed

Material:

Steel comp 301 or steel comp 302b or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 325 or steel comp 330 or steel comp 330a or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Material Specification:

66 federal standard all material responses

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0