# NSN 5320-01-084-9232

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-084-9232

## Fastener Length:

Between 0.802 inches and 0.822 inches

## Head Style:

Undersized oval countersunk

## Head Height:

Between 0.003 inches and 0.005 inches

## Shank Diameter:

Between 0.155 inches and 0.158 inches

#### Shank Style:

Straight w/radius chamfered tip

## Head Major Diameter:

Between 0.2251 inches and 0.2469 inches

## Head Minor Diameter:

0.185 mils and 0.195 centimeters

## **Countersink Height:**

0.0372 inches

## **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

## **Special Features:**

Color violet

## Heat Treatment:

T-81 solution heat treated

## Material:

Aluminum alloy 2219

## **Material Specification:**

Qq-a-430 federal specification single material response

## Surface Treatment:

Anodize

## Surface Treatment Specification:

Mil-a-8625, type 2, class 2 military specification single treatment response

#### Shelf Life:

N/a

## Unit Of Measure:

```
--
```

## Demilitarization:

No

## Fiig:

A040a0

## Mil-std (military Standard):

Mil-a-8625 spec.