

View Online at <https://aerobasegroup.com/nsn/5320-01-085-1238>

Fastener Length:

Between 0.177 inches and 0.197 inches

Head Style:

Universal

Head Height:

Between 0.067 inches and 0.077 inches

Shank Diameter:

Between 0.156 inches and 0.160 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.302 inches and 0.322 inches

Expansion Device:

Serrated stem-type w

End Application:

Ws: engine, aircraft, j-57 all models (c-135, ec-135, b-52; aircraft, phantom f-4; engine, aircraft tf33-p-3/5/9 (c/ec-135, b-52h); aircraft, stratolifter c-135; aircraft, stratofortress b-52; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, ac-130h, mc-130h, ec-130e, hc-130; aircraft, hercules c-130; engine, aircraft, tf-33-p-7 (c-141a/b)

Grip Length:

Between 0.031 inches and 0.062 inches

Special Features:

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

Material:

Steel comp 8740 stem

Material Specification:

Qq-a-430 federal specification single material response sleeve

Surface Treatment:

Cadmium stem and chromate stem

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.