NSN 5320-01-085-3320

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-085-3320

view Offilite at https://aerobasegroup.com/hist//5020-01-000-0020
Fastener Length:
Between 0.564 inches and 0.584 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.125 inches and 0.129 inches
Head Major Diameter:
0.229 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.438 inches and 0.500 inches
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating
visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.
Material:
Steel comp 8740 stem
Material Specification:
Qq-a-430 federal specification single material response sleeve
Surface Treatment:
Cadmium stem and chromate stem
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response stem
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-c-5541 spec.