# NSN 5320-01-085-3320

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-085-3320

# Fastener Length:

Between 0.564 inches and 0.584 inches

# Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.125 inches and 0.129 inches

# Head Major Diameter:

0.229 inches

#### **Expansion Device:**

Serrated stem-type w

# Grip Length:

Between 0.438 inches and 0.500 inches

# **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

# **Special Features:**

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating

visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply. **Material:** 

Steel comp 8740 stem

#### **Material Specification:**

Qq-a-430 federal specification single material response sleeve

#### Surface Treatment:

Cadmium stem and chromate stem

# Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response stem

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A040a0

#### Mil-std (military Standard):

Mil-c-5541 spec.