NSN 5320-01-085-4561

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-085-4561 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.996 inches and 1.021 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3403 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.508 inches Tip Diameter: 0.3306 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.615 inches and 0.630 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 190000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 431 **Material Specification:** Ams 5628 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-085-4561

Pin-rivet - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A528u0