NSN 5320-01-085-8429

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-085-8429 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.410 inches and 1.430 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.5604 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.880 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 132000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-085-8429

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0