## NSN 5320-01-086-1144

Blind Rivet - Page 1 of 1

Mil-std (military Standard):

Mil-c-5541 spec.



View Online at https://aerobasegroup.com/nsn/5320-01-086-1144 **Fastener Length:** Between 0.627 inches and 0.647 inches **Head Style:** Universal **Head Height:** Between 0.080 inches and 0.090 inches **Shank Diameter:** Between 0.188 inches and 0.192 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.365 inches and 0.385 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.438 inches and 0.500 inches **Special Features:** Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply. Material: Steel comp 8740 stem **Material Specification:** Qq-a-430 federal specification single material response sleeve **Surface Treatment:** Cadmium stem and chromate stem **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification all treatment responses stem Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A040a0