

View Online at <https://aerobasegroup.com/nsn/5320-01-086-1145>

Fastener Length:

Between 0.690 inches and 0.710 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.188 inches and 0.192 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.357 inches

Expansion Device:

Serrated stem-type w

End Application:

Wsd: aircraft, stratolifter c-135; aircraft, hornet f/a-18; aircraft, hercules c-130; aircraft, ac-130h, mc-130h, ec-130e, hc-130; aircraft, thunderbolt ii, a-10; cryogenic systems; helicopter observation (ahip), oh-58d; aircraft, phantom f-4; aircraft, f-16; low altitude navigation and targeting infra red system (lantirn)

Grip Length:

Between 0.501 inches and 0.562 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Material:

Steel comp 8740 stem

Material Specification:

Qq-a-430 federal specification single material response sleeve

Surface Treatment:

Cadmium stem and chromate stem

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.