

View Online at <https://aerobasegroup.com/nsn/5320-01-086-1145>

**Fastener Length:**

Between 0.690 inches and 0.710 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.188 inches and 0.192 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

0.357 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

Wsd: aircraft, stratolifter c-135; aircraft, hornet f/a-18; aircraft, hercules c-130; aircraft, ac-130h, mc-130h, ec-130e, hc-130; aircraft, thunderbolt ii, a-10; cryogenic systems; helicopter observation (ahip), oh-58d; aircraft, phantom f-4; aircraft, f-16; low altitude navigation and targeting infra red system (lantirn)

**Grip Length:**

Between 0.501 inches and 0.562 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential

**Material:**

Steel comp 8740 stem

**Material Specification:**

Qq-a-430 federal specification single material response sleeve

**Surface Treatment:**

Cadmium stem and chromate stem

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification all treatment responses stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-c-5541 spec.