

View Online at <https://aerobasegroup.com/nsn/5320-01-086-3597>

**Fastener Length:**

Between 0.439 inches and 0.459 inches

**Head Style:**

Universal

**Head Height:**

Between 0.054 inches and 0.064 inches

**Shank Diameter:**

Between 0.125 inches and 0.129 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.240 inches and 0.260 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

Aircraft, phantom f-4; low altitute navigation & targeting infrared system (lantrin); aircraft, hercules c-130; milstar system; f414 engine (f/a-18 f& g aircraft); aircraft, ac-130h, mc-130h, ec-130e, hc-130; helicopter, mh-53e; helicopter, advance attack, ah-1w; aircraft, stratolifter c-135; aircraft, stratofortress b-52

**Grip Length:**

Between 0.313 inches and 0.375 inches

**Special Features:**

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

**Material:**

Steel comp 8740 stem

**Material Specification:**

Qq-a-430 federal specification single material response sleeve

**Surface Treatment:**

Cadmium stem and chromate stem

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-c-5541 spec.