

View Online at <https://aerobasegroup.com/nsn/5320-01-086-3597>

Fastener Length:

Between 0.439 inches and 0.459 inches

Head Style:

Universal

Head Height:

Between 0.054 inches and 0.064 inches

Shank Diameter:

Between 0.125 inches and 0.129 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.240 inches and 0.260 inches

Expansion Device:

Serrated stem-type w

End Application:

Aircraft, phantom f-4; low altitute navigation & targeting infrared system (lantrin); aircraft, hercules c-130; milstar system; f414 engine (f/a-18 f& g aircraft); aircraft, ac-130h, mc-130h, ec-130e, hc-130; helicopter, mh-53e; helicopter, advance attack, ah-1w; aircraft, stratolifter c-135; aircraft, stratofortress b-52

Grip Length:

Between 0.313 inches and 0.375 inches

Special Features:

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

Material:

Steel comp 8740 stem

Material Specification:

Qq-a-430 federal specification single material response sleeve

Surface Treatment:

Cadmium stem and chromate stem

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.