## NSN 5320-01-086-4963

Blind Rivet - Page 1 of 1

Mil-std (military Standard):

Mil-c-5541 spec.



View Online at https://aerobasegroup.com/nsn/5320-01-086-4963 **Fastener Length:** Between 0.658 inches and 0.678 inches **Head Style:** Universal **Head Height:** Between 0.067 inches and 0.077 inches **Shank Diameter:** Between 0.156 inches and 0.160 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.302 inches and 0.322 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.501 inches and 0.562 inches **Special Features:** Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply. Material: Steel comp 8740 stem **Material Specification:** Qq-a-430 federal specification single material response sleeve **Surface Treatment:** Cadmium stem and chromate stem **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response stem Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A040a0