NSN 5320-01-086-6448

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-086-6448 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.073 inches and 1.093 inches **Head Style:** Err-090 **Head Height:** 0.063 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style: Head Major Diameter:** 0.416 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Unable To Decode:** Unable to decode and unable to decode **Grip Length:** 0.693 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 431 **Material Specification:** Ams 5628 assn standard single material response or mil-s-18732 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:**

Unjf

Thread Series Designator:

258, fscm 73197 mfr ref single treatment response

NSN 5320-01-086-6448

Pin-rivet - Page 2 of 2



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.