## NSN 5320-01-087-8846

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-087-8846 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.253 inches and 2.273 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.3813 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.943 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-087-8846

Pin-rivet - Page 2 of 2



Fiig:

A528u0